

INCIDENT MARKING  
FLARE, AUTO-FIRING

ASBESTOS CORE

EMF CORE SHIELD

FALSE TX/RX WIRE  
(FLARE FUSE)

**FIRESTIK III**  
"TERMINATOR SPECIAL"

**APPROVED**  
U.S. DEPARTMENT OF DEFENSE

**MEETS OR EXCEEDS CIA  
REQUIREMENTS FOR  
RADIOACTIVE DEVICES**

TRIGGER PIVOT

SAFETY FULCRUM

RF TIMER

PLUTONIUM TRIGGER

TRIGGER GUIDE

URANIUM CORE

SAFETY FULCRUM

RF ACTIVATOR

RF FUSE

TITANIUM COUPLER

**WARNING!** Do not attempt to test operational function of this device. Fusion will occur on first attempt to use this strategic apparatus. There are NO safety mechanisms. Automatic triggering occurs above 8 watts or when transmit frequency is below 26.965 MHz or above 27.405 MHz.

**INSTALLATION:** Remove existing antenna and replace with FSIII. Unless absolutely sure of transmitter output, it is not advisable to measure or set SWR. Effectively vaporizes all matter within a 0.5 kilometer radius at ground zero.

RV1 V63-NUKE.SKD

Firestik Antenna Company  
2614 E Adams St.  
Phoenix, AZ 85034-1495  
(T) 602-273-7151 (F) 602-273-1836  
E-Mail: Eng@firestik.com

Unless otherwise specified, all  
dimensions are shown in inches

Tolerance

$x = \pm .1$   
 $.xx = \pm .03$   
 $.xxx = \pm .010$

Angles

Desc: **TERMINATOR CB ANTENNA**

Scale .25 : 1 Part # **FSIII**

By: RV1

Date: **01-APR-97**

Rev:

Page 1 of 1